

(April 3, 2006)

Light Standards with Type 1 Luminaire Arms

Lighting standards shall be fabricated in conformance with the methods and materials specified on the pre-approved plans listed below, provided the following requirements have been satisfied:

(a) Mounting heights shall be as specified in the Plans.

(b) Light source to pole base distances (H1) shall be determined or verified by the Engineer prior to fabrication. Fabrication tolerance shall be ± 6 inches.

(c) All other requirements of the Special Provisions have been satisfied.

<u>Pre-Approved Plan</u>	<u>Fabricator</u>	<u>Mounting Hgt.</u>
Drawing No. DB00654 Rev. A Sheets 1, 2 & 3	Valmont Ind. Inc.	30', 40' & 50'
Drawing No. W3721-1 Rev. E & W3721-2 Rev. A	Ameron Pole Prod. Div.	40' & 50'
Drawing No. NWS 3510 Rev. 4-6-04 or NWS 3510B Rev. 4-6-04	Northwest Signal Supply Inc.	25', 30', 35', 40', 45' & 50'
Drawing WS-SL-01	American Pole Structures, Inc.	25', 30', 35', 40', 45', 50'
Drawing 71035-B39 Rev. 2 Sheets 1 & 2	Union Metal Corp.	40'
Drawing 71035-B38 Rev. 2 Sheets 1 & 2	Union Metal Corp.	50'
Drawing No. WSDOT-LP-01 Rev. 2, Sheets 1 and 2 or WSDOT - LP-01-BE Rev 0 Sheets 1 and 2 or WSDOT - LP-01-C8B Rev 0	West Coast Engineering Group	25', 30', 35', 40', 45', and 50'